

ORC-LFT

ITEM NO: 12598

The Orcomm Lift/Elevator Controller is versatile and robust, suitable for both residential and commercial environments. It supports Wiegand, RS485, and TCP/IP communication, ensuring flexible connectivity. Each controller can be integrated with our Advanced Management Software or operated independently via a web server client. It manages up to 16 zones, expandable to 32 with an additional board, and supports multiple verification methods.

Fire alarm inputs provide critical functionality for opening or closing doors during emergencies. The controller also features eight group timing functions for managing timed zones and access groups, such as restricting user access to Monday through Friday only.



SPECIFICATION

Size	218mm×130mm×23mm	Colour	Deep blue
Weight	0.22kg	Box	285mm×240mm×82mm
Box Colour	Black	Box Weight	2.4kg
Temperature	<60°C	Humidity	10% ~ 95% R.H
Voltage	DC 12V	Current	< 300mA
Power	≤5W	Power Off Protection	10 years
Card holder	120000	Logs	200000
Floor Capacity	16	Communication	TCP/IP
Communication Distance	100 meters between access controller and HUB	Card Reading	N/A
Communication	100 meters	Door opening methods	Card, password, card+password, double bard, first card opening, software, fire alarm, release button, timing door opening
Card Readers	2x Wiegand	Alarm Output	N/A
Alarm Input	1	Fire Alarm Output	1
Fire Alarm Input	1	Elevator Button	16
Door Sensor Input	1	Control Input	16